

B2B PROJECT RESOURCE

Cabinet Installation Dimensions Guide

Planning reference for built-in, wall-mounted and pull-out ironing board projects.

September 2026 | Revision 1.0

What should cabinet manufacturers confirm before machining?

Confirm the exact model, current technical drawing, clear internal dimensions, mounting-panel construction, hinge and shelf interference, operating path, installed height and service access before drilling or machining.

Built-in cabinet planning dimensions

Planning point	Confirmed reference
Ironing surface	810 × 335 × 25 mm (31-7/8 × 13-1/8 × 1 in)
Frame	715 × 305 × 65 mm (28-5/32 × 12 × 2-17/32 in)
Minimum clear internal width	449 mm (17-11/16 in) at the vertical storage position
Approximate vertical clearance	1480 mm (58-9/32 in) for the stored assembly shown in the installation guide
Positioning	180° horizontal range; working surface rotates 90° during deployment
Mounting side	Left or right side of a suitable cabinet compartment

The cabinet must be securely fixed and the mounting wall must be suitable for the selected fasteners. Hinges, shelves, doors and adjacent fittings must not obstruct the full opening path.

Four-stage installation planning

- Verify the compartment and full movement envelope against the current drawing.
- Fix the mounting plate to a reinforced cabinet wall with fasteners selected for the cabinet construction.
- Fasten the work surface to the frame using the specified washers and hex-key fittings.
- Set a comfortable installed height, test the complete movement and confirm that all fasteners remain secure. The source manual recommends two installers.

Wall-mounted and pull-out planning references

Type	Reference	Key dimensions	Operation	Typical project fit
180° wall-mounted	33.35.30100200	950 × 300 × 185 mm	Double fold; 180° swivel	Hotels, apartments, laundry rooms
Wall-mounted fold-down	33.36.30400300	1070 × 300 × 35 mm	Vertical fold-down	Laundry and utility rooms
Cabinet built-in	33.35.30600100	Board 810 × 335 × 25 mm; frame 715 × 305 × 65 mm	Vertical storage; 180° horizontal positioning	Wardrobes, closets, fitted cabinetry
Folding pull-out	33.35.30200200	Open approx. 956 × 710 × 110 mm; stored approx. 500 × 350 × 110 mm	Ball-bearing pull-out; fold; up to 180°	Cabinet and wardrobe pull-outs

Pre-order cabinet checklist

- Selected product and reference item number
- Dimensioned cabinet drawing with material and panel thickness
- Door, hinge, shelf and drawer locations
- Desired working height and user-clearance zone
- Fixing method and reinforcement design approved by the cabinet installer
- Access for future cover replacement and mechanism service
- Requested finish, cover, branding, packaging and destination

Specification control

Dimensions in this guide are planning references from the supplied product documents. They are not a substitute for the current order-specific drawing. Confirm the revision and all critical dimensions with VENACE before production or cabinet machining.