

B2B PROJECT RESOURCE

Ironing Board Specification & Installation Pack

Reference specifications and installation-planning notes for four VENACE project formats.

September 2026 | Revision 1.0

Confirmed planning specifications

Type	Reference	Key dimensions	Operation	Typical project fit
180° wall-mounted	33.35.30100200	950 × 300 × 185 mm	Double fold; 180° swivel	Hotels, apartments, laundry rooms
Wall-mounted fold-down	33.36.30400300	1070 × 300 × 35 mm	Vertical fold-down	Laundry and utility rooms
Cabinet built-in	33.35.30600100	Board 810 × 335 × 25 mm; frame 715 × 305 × 65 mm	Vertical storage; 180° horizontal positioning	Wardrobes, closets, fitted cabinetry
Folding pull-out	33.35.30200200	Open approx. 956 × 710 × 110 mm; stored approx. 500 × 350 × 110 mm	Ball-bearing pull-out; fold; up to 180°	Cabinet and wardrobe pull-outs

Model details

Reference	Material / finish	Weight and packing reference
33.35.30100200	Metal support frame; heat-resistant cotton cover; white paint	NW/GW 10.50/11.10 kg; carton 600 × 400 × 190 mm; 1 pc
33.36.30400300	Metal frame; heat-resistant cover; white paint	NW/GW 4.8/5.5 kg; package 1100 × 310 × 50 mm

Reference	Material / finish	Weight and packing reference
33.35.30600100	Iron/thick-walled metal frame; removable heat-resistant cotton cover	NW/GW 6.2/7.0 kg; package 850 × 360 × 110 mm
33.35.30200200	Metal frame; perforated support; ball-bearing rails; white paint	Reference NW/GW 10/11.1 kg; carton 600 × 400 × 190 mm; 1 pc

Installation notes

- Use a suitable structural wall, wall reinforcement or reinforced cabinet panel.
- Choose fasteners for the actual wall or cabinet construction; generic fasteners are not automatically suitable for every substrate.
- Keep the full movement path clear of doors, hinges, shelves, drawers and adjacent appliances.
- Set a comfortable working height for the intended users and project conditions.
- After installation, cycle the mechanism through all positions and recheck fasteners, locking points and clearances.
- Retain the current drawing and installation instructions with the project handover documents.

Product-specific planning notes

180° wall-mounted

Allow approximately 950 mm of board projection plus user circulation. The double-folding board can be positioned through a 180° range. Confirm a suitable structural fixing zone.

Wall-mounted fold-down

Allow a 1070 × 300 mm working surface and vertical storage height. Confirm that the wall and fasteners are appropriate for the installation.

Cabinet built-in

Use at least 449 mm clear internal width at the vertical storage position and approximately 1480 mm of vertical clearance, subject to the current drawing. The source installation guide recommends two installers.

Folding pull-out

Plan around an approximate stored footprint of 500 × 350 × 110 mm and an approximate open overall size of 956 × 710 × 110 mm. Confirm rail, door, drawer and rotation clearances.

Document control

Specifications can change. Request the current model drawing, installation instruction and packing confirmation before order approval or cabinet machining.